

# CPS LED LIGHTING

Applications:

Warehouses

Hazardous Locations

Mining Facilities

Combustible Areas

Construction Zones



40W~60W



80W~150W

## Explosion-Proof Linear

The Explosion-Proof Linear is built to withstand critical environments, providing reliable lighting in environments where volatile liquids, gases, and vapors are present. With a consistent output, high waterproof rating, and resistant design, this fixture is perfect for the toughest of jobs.

## ORDER INFORMATION

SERIES	WATTAGE (W)	VOLTAGE UL = 100-277V	KELVIN 50=5000K
CPS-EXPL-	40W	UL	40/50
CPS-EXPL-	60W	UL	40/50
CPS-EXPL-	100W	UL	40/50
CPS-EXPL-	150W	UL	40/50
<b>EXAMPLE: CPS-EXPL-40W-UL-40</b>			
DLC Model# CPS-EXPL-40W-UL-40			

## SPECIFICATIONS

Offered in 40-150 watts

Several mounting options: U-bracket, Ceiling mount, Wall mount

1-10V Dimming available

Motion sensor, photocell, and control options available

IP66 rating, damp and wet locations

Long lifespan

Instant start, no flickering, no humming

Green and eco-friendly, without mercury



CPS LED LIGHTING

843-407-6803

SALES@CPSLED.COM


WWW.CPSLED.COM

# CPS LED LIGHTING

## TECHNICAL CHARACTERISTICS

Color temperature	4000K, 5000K
Input voltage	AC100-277 50/60Hz
Lumen efficiency	120 LM/W
Waterproof rating	IP66
CRI	>70
PFC	>0.9
Viewing angle	120°
Application	Indoor/Outdoor
L70 Life	Projected 100,000 hours
Warranty	7 years



### Photometric:



# CPS LED LIGHTING

## MATERIALS


Housing	Die Cast Aluminum
Lens	High Transmittance Tempered Glass
Mounting	U-Bracket, Ceiling mount, Wall Mount



## PACKAGING INFORMATION

PRODUCT MODEL	PRODUCT SIZE	CARTON SIZE	QTY/CTN	NET WEIGHT	GROSS WEIGHT
CPS-EXPL-40W-UL-XX	23.46*4.96*4.48	26.57*8.07*9.25	1	18.6	20.17
CPS-EXPL-60W-UL-XX	23.46*4.96*4.48	26.57*8.07*9.25	1	18.6	20.17
CPS-EXPL-100W-UL-XX	22.28*7.95*4.40	25.39*11.22*9.44	1	23.3	24.9
CPS-EXPL-150W-UL-XX	22.28*7.95*4.40	25.39*11.22*9.44	1	23.3	24.9

### Ceiling Mount:



### Wall Mount:

