CPS LED LIGHTING

Applications:

- Gas stations
- Service stations
- Underground parking lots

Garages



Macro Linear Highbay

The Linear Highbay is the lighting solution for a wide variety of applications and mounting heights. Precision designed optics, multiple distributors, and a choice of lumen outputs and color temperatures makes the energy efficient linear highbay. The ideal solution for industrial, commercial, and other highbay applications.

ORDER INFORMATION							
SERIES	LENGTH (FT)	WATTAGE	VOLTAGE UL=100-277V	KELVIN 50=5000K			
CPS-MLHB-	2-	90W-	UL-	40			
	2-	162W-	UL-	50			
	2-	223W-	UL-				
	4-	321W-	UL-				




CPS LED LIGHTING 843-407-6803 SALES@CPSLED.COM WWW.CPSLED.COM


CPS LED LIGHTING

TECHNICAL CHARACTERISTICS					
Color temperature	4000K, 5000K				
Input voltage	AC100-277 50/60Hz				
Lumen efficiency	130 LM/W				
CRI	>80				
PFC	>0.9				
Operating temperature	-4°F to 122°F				
Application	Indoor/Outdoor				
L70 Life	Projected 100,000 hours				
Warranty	7 years				

Photometric:



DIMENSIONS							
PART NO.	LENGTH	WIDTH	DEPTH	WEIGHT (LB)			
CPS-MLHB-2-90W	23.8	12.6	3.6	10.14			
CPS-MLHB-2-90W	23.8	12.6	3.6	10.14			
CPS-MLHB-2-223W	23.8	17.3	3.6	12.56			
CPS-MLHB-4-321W	45.9	12.6	3.6	17.85			





CPS LED LIGHTING 843-407-6803 SALES@CPSLED.COM WWW.CPSLED.COM