

# CPS LED LIGHTING



**PRODUCT NAME :** Compact Tunable Strip  
**PRODUCT SKU EX:** CPS-TSTR-4-18/25/30W-UL-3550

### PRODUCT DESCRIPTION

This series is an upgrade to our previous tunable strip light. It provides faster surface mounting or row mounting, luminous part can be easily removed to add emergency backup options or sensors.  
 Tunable/ Adjustable in power wattage and color temperature.

APPLICATIONS
Shops, Retail spaces, Medical, Industrial, Commercial.

ORDERING INFORMATION				
SERIES	SIZE	WATTAGE	VOLTAGE	CCT
CPS-TSTR-	2-	15/20/25W-	UL-	3550
CPS-TSTR-	4-	18/25/30W-	UL-	3550
CPS-TSTR-	8-	65/75/90W-	UL-	3550
UL=120-277V / UH=277-480V				

CERTIFICATIONS & RATINGS
IP20
DLC: yes
UL: yes
ETL: no
NSF: no
CPS RECOMMENDATIONS:
EMB: available
CONTROL: available
SENSOR: available

SPECIFICATIONS
LM/W: 130
Warranty: 5
Dimming: 1-10V
Temperature Rated: -20°C/-4°F to 50°C /122°F
Lens: sheet metal stamping
Voltage: UL = 120-277V
CCT: 3500K-5000K
Mounting: surface mount
L70: 100,000 hours

### DIMENSIONS & PHOTOMETRICS

ITEM	LENGTH	WIDTH	DEPTH
2FT	22.2"	1.9"	2.4"
4FT	47.3"	1.9"	2.4"
8FT	94.2"	1.9"	2.4"

Part #	Luminous	Input Power	Efficacy	Input Voltage
CPS-TSTR-2-15/20/25W-UL-3550	3300	25	132	120-277
	3550	25	142	120-277
	3350	25	134	120-277
	2760	20	138	120-277
	2960	20	148	120-277
	2800	20	140	120-277
	2145	15	143	120-277
	2295	15	153	120-277
	2175	15	145	120-277

Part #	Luminous	Input Power	Efficacy	Input Voltage
CPS-TSTR-4-18/25/30W-UL-3550	3960	30	132	120-277
	4260	30	142	120-277
	4020	30	134	120-277
	3450	25	138	120-277
	3700	25	148	120-277
	3500	25	140	120-277
	2592	18	144	120-277
	2772	18	154	120-277
	2628	18	146	120-277

CPS-TSTR-8-65/75/90W-UL-3550	11970	90	133	120-277
	12870	90	143	120-277
	12150	90	135	120-277
	10425	75	139	120-277
	11175	75	149	120-277
	10575	75	141	120-277
	9295	65	143	120-277
	9945	65	153	120-277
	9425	65	145	120-277