

## CPS LED LIGHTING



**PRODUCT NAME :** Tunable Flood Lights  
**PRODUCT SKU EX:** CPS-TFL-150W-UL-XXK

### PRODUCT DESCRIPTION

Available in two sizes, wattage packages range from 75W - 300W so that it can meet various applications. TFL offers field adjustable color temperature and power option. Various mounting options available including slipfitter mount, yoke mount, and wall mount for flexible installations. IP66 rated. 100%, 75%, 50%, 25% selectable/dimmable.

### APPLICATIONS

Outdoor applications  
 Warehouses  
 Building exteriors  
 Stadiums  
 Gymnasiums  
 Supermarkets

### ORDERING INFORMATION

SERIES	WATTAGE	VOLTAGE	CCT
CPS-TFL	75W-	UL-	XXK
CPS-TFL	150W-	UL-	XXK
CPS-TFL	300W-	UL-	XXK

### CERTIFICATIONS & RATINGS

IP66/ IK08
DLC: YES
UL: NO
ETL: YES
NSF: NO
<b>CPS RECOMMENDATIONS:</b>
EMB: available
CONTROL: available
SENSOR: available

### SPECIFICATIONS

Warranty: 5 Years
Lumens: 150 LM/W
Beam Angle: 65x95°NEMA
Luminous Flux: 75W (11250LM), 150W (22500 LM), 300W (45000LM)
Driver type: constant current
Color temperature: 3000K, 4000K, 5000K adjustable
Color Rendering Index: Ra70
Operating Temperature: -30°C to + 50°C (-22°F to 113°F)
Material & Finish: Aluminum alloy, Akzo powder coating, Black/Bronze
L70 Life: 100,000 hours
Control: Dimmable, Photocell:
Mounting: Slipfitter, Yoke, Trunnion

### DIMENSIONS & PHOTOMETRICS

Dimensions			
	75W	150W	300W
Product	233x187x141mm (8.8"x7.4"x5.6")		469x187x185mm(18.5"x7.4"x7.3")
Net Weight	3.4kg (7.48Lbs)		7.9kg (17.38Lbs)
Carton	310x305x255mm (11.8"x12"x10")		540x310x255mm(21.3"x12.2"x10")
Gross Weight	5kg (11Lbs)		9.6kg (21Lbs)

