

CPS LED LIGHTING



PRODUCT NAME : Tunable Wallpack
PRODUCT SKU EX: CPS-TWP-100W-UL-BL-500K

PRODUCT DESCRIPTION

The tunable wallpack is versatile and efficient with a high end design. Power and CCT tunable helps to reduce sku's and fit many applications. Easy installations without opening the driver box and accessories available.

APPLICATIONS
Entrance lighting Courtyards Outdoor landscape Industrial Hotels

ORDERING INFORMATION				
SERIES	WATTAGE	VOLTAGE	HOUSING	CCT
CPS-TWP-	27W-	UL-	BL-	3000/4000/5000K
CPS-TWP-	45W-	UL-	BL-	3000/4000/5000K
CPS-TWP-	62W-	UL-	BL-	3000/4000/5000K
CPS-TWP-	70W-	UL-	BL-	3000/4000/5000K
CPS-TWP-	100W-	UL-	BL-	3000/4000/5000K

CERTIFICATIONS & RATINGS
IP65
DLC: yes
UL: yes
ETL: no
NSF: no
CPS RECOMMENDATIONS:
EMB: available
CONTROL: available
SENSOR: available

SPECIFICATIONS
120-277VAC Input Voltage (UL)
1-10V Dimming:
Power factor: > 90%, THD <20%
Operation Temperature Range: -40°C to 40°C (-40°F - + 104°F)
Operating with emergency battery temperature range: 10°C to 40°C (+50°F-+ 104°F)
Lumen output adjustable: 3,200 - 13,200 LM
UV stabilized polycarbonate and glass are both available for the optic lens
Sealed die casting profile for outdoor applications
Suitable for applications requiring 3G vibration tests according to ANSI C136.31
MOUNWarranty: 5 yearsTING:
CRI: 70
Accessories available: photocell, sensors, emergency backup

DIMENSIONS & PHOTOMETRICS

Adjustable lumen output

		27W		45W		62W		70W		100W	
SETTING	DIFFUSER	SYSTEM WATTS	LUMENS (5000K)	SYSTEM WATTS	LUMENS (5000K)	SYSTEM WATTS	LUMENS (5000K)	SYSTEM WATTS	LUMENS (5000K)	SYSTEM WATTS	LUMENS (5000K)
100%	PC Diffuser	26.60	3469.90	45.22	5495.70	63.73	7814.20	71.61	9246.60	100.90	12468.10
80%	PC Diffuser	20.77	2805.82	33.79	4341.60	52.19	6640.51	53.90	7434.27	78.80	10160.25
60%	PC Diffuser	15.38	2163.14	26.24	3527.69	39.29	5255.05	41.63	6018.61	61.62	8581.79
40%	PC Diffuser	9.86	1428.21	17.76	2514.28	26.07	3675.80	27.89	4257.13	40.83	6089.42
100%	Glass Diffuser	26.65	3323.90	45.17	5404.30	63.54	7712.70	70.26	9106.60	100.00	12216.90
80%	Glass Diffuser	20.81	2687.71	33.75	4269.40	52.03	6554.25	52.88	7321.71	78.10	9955.55
60%	Glass Diffuser	15.41	2072.12	26.21	3469.02	39.17	5186.79	40.85	5927.49	61.07	8408.89
40%	Glass Diffuser	9.88	1368.12	17.74	2472.47	25.99	3628.05	27.36	4192.68	40.47	5966.73

