

	Product Name	200W Pres-sure Light	
	Item No.	CPS-PSL-200W-UL-50	
Optical Data		Electrical Data	
		Power Supply	MeanWell
System Efficacy	130LM/W±5%(CCT=5000K)	Input Voltage	100~277VAC
Luminous Flux	26000LM±5%(CCT=5000K)	Power Frequency	50/60Hz
CCT	5000K	Output Voltage	28.8~48VDC
Beam Angle	90°	Output Current	4.4A(Constant Current)
CRI	>80Ra	Power Efficiency	>92%
System Efficiency	>92%	Power Factor	>0.95
		Total Harmonic Distortion	<15%
Others			
System Power Consumption	200±5W	Junction Temperature(Tj)	<85°C(Ta=30°C)
LED Power Consumption	184±5W	Storage Temperature	-40~+70°C
Fixture Material	Aluminum Alloy	Operating Temperature	-30~+50°C
Ingress Protection	IP66 IP69K	Operating Humidity	15~90%RH
Luminaire Net Weight	7.2±0.3kg	Outlook Dimensions	φ489×200mm
Life Span	>50000Hrs(Ta=30°C @L70)	Export Carton Size	L560*W260*H565mm
Certification	UL DLC NSF	Warranty	7 years
Optional Info.			
Fixture Color	White (stocked), Silver	Installation Method	Loop Hanging
Intelligent Control	Dimmable		
Physical Dimensions		Light Distribution Curve	
			