EVC10 Level 2 Up to 80A

Pure PC material, Anti-UV treatment, and over 3 years' yellow resistance

Black

Silver

IK08 & Type 3 enclosure for indoor & outdoor use

RFID reader (ISO14443A), QR code is available

80A to 48A, or 48A to 16A adjustable

LAN standard, 4G or Wi-Fi optional

4.3" LCD screen compliant with CTEP

OCPP 1.6J, Connected successfully with 30+ global EVC platforms

Model No.	EVC10/16AC	EVC10/32AC	EVC10/40AC	EVC10/48AC	EVC10/70AC	EVC10/80AC
Input Voltage	208-240Vac					
Frequency	50-60Hz					
Amperage	16A	32A	40A	48A	70A	80A
Max. Power Output	3.8kW	7.6kW	9.6kW	11.5kW	16.8kW	19.2kW
Net Weight	13.8lbs	13.8lbs	16.8lbs	18.1lbs	19.8lbs	19.8lbs
Gross Weight	16.1lbs	16.1lbs	19.0lbs	20.3lbs	22.5lbs	22.5lbs
Product Dimensions	13.8″ x 9.8″ x 5.1″					
Package Dimensions	19.6″ x 13.7″ x 10.7″				19.6″ x 13.7″ x 12.4″	
Protection & Standard						
Charging Interface	SAE J1772 Compliant, Type 1 Plug					
Safety Compliance	UL2594, UL2231-1/-2					
Multiple Protection	UVP, OVP, RCD (CCID 20), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection					
Environmental						
Operating Temp.	-22°F to 122°F					
Relative Humidity	Up to 95% non-condensing					
Cable Length	18ft Standard (25ft Optional with Surcharge)					