



**EVC11** / Level 2 / ISO/IEC 15118



Pure PC material, Anti-UV treatment, and over 3 years' yellow resistance

ISO/IEC 15118 plug & charge

IK08 & Type 3 enclosure for indoor & outdoor use

LAN standard, 4G or Wi-Fi optional

80A to 48A, or 48A to 16A adjustable

OCPP 1.6J, Successfully connected with 30+ global EVC platforms

Specified screws & tool for security

RFID reader (ISO14443A)

Model No.	EVC11/16AC	EVC11/32AC	EVC11/40AC	EVC11/48AC	EVC11/70AC	EVC11/80AC
Input Voltage	208-240Vac					
Frequency	50-60Hz					
Amperage	16A	32A	40A	48A	70A	80A
Max. Power Output	3.8kW	7.6kW	9.6kW	11.5kW	16.8kW	19.2kW
Net Weight	12.1lbs	12.1lbs	14.6lbs	15.7lbs	17.2lbs	17.2lbs
Gross Weight	14.6lbs	14.6lbs	17.0lbs	18.1lbs	19.6lbs	19.6lbs
Product Dimensions	14.2" x 9.8" x 3.9"					
Package Dimensions	19.6" x 13.7" x 9.3"				19.6" x 13.7" x 10.5"	
<b>Protection &amp; Standard</b>						
Charging Interface	SAE J1772 Compliant, Type 1 Plug					
Safety Compliance	UL2594, UL2231-1/-2					
Multiple Protection	UVP, OVP, RCD (CCID 20), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection					
<b>Environmental</b>						
Operating Temp.	-22°F to 122°F					
Relative Humidity	Up to 95% non-condensing					
Cable Length	18ft Standard (25ft Optional with Surcharge)					