



EVC12 / Level 2 / Up to 48A



Silver



Black



Pure PC material, Anti-UV treatment, and over 3 years' yellow resistance



Model 1: Plug & Charge Wifi & Bluetooth standard



IK08 & Type 3 enclosure for indoor & outdoor use



Optional model 2: RFID reader (ISO14443A)



48A to 16A by switch, 48A to 6A by TCP server



Optional model 3: OCPP 1.6J



Specified screws and tool for security



Home use APP for better UE

Model No.	CPS-EVC12/16AC	CPS-EVC12/32AC	CPS-EVC12/40AC	CPS-EVC12/48AC
Input Voltage	208-240Vac			
Frequency	50-60Hz			
Amperage	16A	32A	40A	48A
Max. Power Output	3.8kW	7.6kW	9.6kW	11.5kW
Net Weight	12.4lbs	12.4lbs	15.0lbs	16.0lbs
Gross Weight	14.8lbs	14.8lbs	17.2lbs	18.5lbs
Product Dimensions	14.2" x 9.8" x 4.4"			
Package Dimensions	19.6" x 13.7" x 9.9"			
Protection & Standard				
Charging Interface	SAE J1772 Compliant, Type 1 Plug			
Safety Compliance	UL2594, UL2231-1/-2			
Multiple Protection	UVP, OVP, RCD (CCID 20), SPD, Ground Fault Protection OCP, OTP, Control Pilot Fault Protection			
Environmental				
Operating Temp.	-22°F to 122°F			
Relative Humidity	Up to 95% non-condensing			
Cable Length	18ft Standard (25ft Optional with Surcharge)			