

## PRODUCT FEATURES:

- THE LINEAR HIGH BAY IS THE LIGHTING SOLUTION FOR A WIDE VARIETY OF APPLICATIONS AND MOUNTING HEIGHTS.
- PRECISION DESIGNED OPTICS
- UL 1598 SUITABLE DAMP LOCATIONS
- UL 8750 LED EQUIPMENT IN LIGHTING

### APPLICATIONS

INDUSTRIAL
COMMERCIAL
HIGH BAY APPLICATIONS
WAREHOUSE
RETAIL



### DIMENSIONS (IN)

<u>PART NO.</u>	<u>LENGTH</u>	<u>WIDTH</u>	<u>DEPTH</u>	<u>WEIGHT</u>
CPS-SLHB-2-85W	24.8	15	2.2	10 LBS
CPS-SLHB-2-155W	24.8	15	2.2	10 LBS
CPS-SLHB-2-210W	24.8	18.9	2.2	11.3 LBS
CPS-SLHB-4-300W	46.5	18.9	2.2	20 LBS

### OPTIONAL ACCESSORIES

V HOOK
V HOOK + CHAIN
CABLE
WIREGUARD
SURFACE
PENDANT
SUSPENDING
EMERGENCY



### ORDER INFORMATION

SERIES	LENGTH (FT)	WATTAGE	VOLTAGE UL = 100-277V	COLOR TEMP (CCT)	
CPS-SLHB-	2	85W	UL	50	
	2	155W	UL	50	
	2	210W	UL	50	As seen on DLC as: (CPS-SLHB-4-210W-UL-50)
	4	300W	UL	50	
EXAMPLE: CPS-SLHB-2-155W-UL-50					

### PHOTOMETRIC TEST LIST

<u>PART NO.</u>	<u>LUMENS</u>	<u>WATTS</u>	<u>RATED</u>
CPS-SLHB-2-85W-UL-40	11475	85	136
CPS-SLHB-2-85W-UL-50	11560	85	136
CPS-SLHB-2-155W-UL-40	20925	155	135
CPS-SLHB-2-155W-UL-50	21080	155	136
CPS-SLHB-2-210W-UL-40	28350	210	135
CPS-SLHB-2-210W-UL-50	28560	210	136
CPS-SLHB-4-300W-UL-40	40500	300	135
CPS-SLHB-4-300W-UL-50	40800	300	136