

## U Tubes

## Series CPS-U-T8-



### Suitable Applications:

Commercial  
Municipalities  
Warehouse  
Architectural

<b>Wattage</b>	18W
<b>Luminous Efficiency</b>	140 Lumens / Watt
<b>Length</b>	U Tube
<b>Color Temperature</b>	4000K, 5000K
<b>Operating Temperature</b>	- 40 to125 F
<b>Input Voltage</b>	AC 110 - 277 V
<b>CRI</b>	Ra>85

### Ordering Information

<b>Sample Part Number:</b>		<b>CPS-U-T8-18W-UL-F-50</b>	<b>Series CPS-U-T8-</b>
<b>Lengths</b>		<b>Options</b>	<b>Lens</b>
U	U tube	Dual Mode	Works Both Direct Wire or Ballast Compatible
			C Clear
			F Frosted
<b>Kelvin Temperatures</b>		<b>Voltage</b>	<b>Wattages</b>
40	4000K	UL	110-277 V
50	5000K		18W 18 Watts

**DOES NOT EMIT HARMFUL VAPORS OR GASES AND IS SHATTER RESISTANT**



LM 79  
LM 80

CPS-U-T8-18W-UL-C-40  
CPS-U-T8-18W-UL-C-50

CPS-U-T8-18W-UL-F-40  
CPS-U-T8-18W-UL-F-50