

CPS LED LIGHTING

Applications:

Shops

Retail spaces

Medical

Industrial

Commercial



Lumen Smart Tunable Strip Light



The small size of the strip light makes it an ideal choice for many applications.

Tunable wattage and color temp offers a selection of wattages and kelvin temperatures from 3500K to 5000K.

ORDER INFORMATION

SERIES	LENGTH (FT)	TUNABLE WATTAGE (W)	VOLTAGE UL = 100-277V	TUNABLE COLOR TEMP (CCT)
CPS-LS-TSTR-	2-	15/20/25W	UL-	35/40/50K
CPS-LS-TSTR-	4-	18/25/30W-	UL-	35/40/50K
CPS-LS-TSTR-	8-	65/75/90W-	UL-	35/40/50K

EXAMPLE: CPS-LS-TSTR-4-XXW-UL-XX



DIMENSIONS

PART NUMBER	LENGTH	WIDTH	DEPTH	WEIGHT
CPS-LS-TSTR-2-XXW-UL-XX	22.2"	2.4"	2.8"	2.2 LBS
CPS-LS-TSTR-4-XXW-UL-XX	47.3"	2.4"	2.8"	4 LBS
CPS-LS-TSTR-8-XXW-UL-XX	94.2"	2.4"	2.8"	7.5 LBS



CPS LED LIGHTING

843-407-6803

SALES@CPSLED.COM

WWW.CPSLED.COM

CPS LED LIGHTING

SPECIFICATIONS

UL 1598 SUITABLE FOR DAMP LOCATIONS
UL 8750 LED EQUIPMENT IN LIGHTING PRODUCTS TEMPERATURE RATED AT (-20°C TO +50°C)(-4°F TO 122°F)
0-10V DIMMING TYPE IS CONTINUOUS
CAN DIM TO 10%
V-HOOK READY
SURFACE MOUNTING
FROSTED LENS
7 YEAR WARRANTY
LM/W: 135
L70 LIFE: 100,000 HOURS

PHOTOMETRIC TEST LIST

PART NUMBER	LUMENS RATED	WATTS RATED	EFFICACY RATED	CCT RANGE	
CPS-LS-TSTR-2-15/20/25W-UL-35/40/50K	3275	25	131	835-850	
	3300	25	132		
	3325	25	133		
	CPS-LS-TSTR-2-15/20/25W-UL-35/40/50K	2680	20	134	835-850
		2700	20	135	
		2740	20	137	
		2070	15	138	
		2085	15	139	
CPS-LS-TSTR-4-18/25/30W-UL-35/40/50K	2100	15	140	835-850	
	3930	30	131		35-50K
	3960	30	132		35-50K
	3990	30	133		35-50K
	3350	25	134		35-50K
	3375	25	135		35-50K
	3400	25	136		35-50K
	2484	18	138		35-50K
	2502	18	139		35-50K
2520	18	140	35-50K		
CPS-LS-TSTR-8-65/75/90W-UL-35/40/50K	11790	90	131	35-50K	
	11880	90	132	35-50K	
	11970	90	133	35-50K	
	10275	75	137	35-50K	
	10350	75	138	35-50K	
	10425	75	139	35-50K	
	9100	65	140	35-50K	
	9165	65	141	35-50K	
	9230	65	142	35-50K	



CPS LED LIGHTING

843-407-6803

SALES@CPSLED.COM

WWW.CPSLED.COM