

c(UL)us

- -Ultra bright, energy efficient, long life Red or Green LED
- -Long life, energy efficient.
- -Optional Red or Green LED EXIT signs, SALIDA faceplate available.
- -Overload/Short Circuit Protection
- -Single or double face (Universal).

ELECTRICAL

DIMENSIONS

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and
- push-to -test. switch for mandated code compliance testing.
- 1.2V Long life, maintenance-free, rechargeable Ni-Cd battery.

-Internal solid-state transfer switch automatically connects the internal battery to LED board and LED lamp heads for minimum 90-minute emergency illumination.

-Fully automatic solid-state, two rate charge initiates battery charging to recharge a discharged battery in 24 hours.

CPS-STEE30-30G

MOUNTING

EZ-snap mounting canopy included for top or end mount. Universal K/O pattern on back plate for wall mount.

HOUSING

Injection-molded, engineering grade. 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish. EZ snap-out chevron directional indicators.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery pro-rated for five years.
- meets UL 924
- cULus Listed for damp location(0 ℃-50 ℃)
- Life Safety NFPA 101
- NEC/OSHA
- -T20, CEC/DOE
- Most State and Local Codes

