

CPS LED LIGHTING

Applications:

Industrial facilities

Warehouses

Hazardous locations

Mining facilities

Combustible areas

Construction zones



Explosion Proof Round Highbay


The Explosion Proof series is rated for hazardous, damp, and wet locations.

Different mounting styles are available for a variety of applications. Class I, Division 2, Groups A, B, C and D; Class II, Division 2, Groups F and G; Class III.

This series is only made to order items. Please refer to the ordering information below for the wattages offered. Motion sensor, photocell, & control options available. IP66 Rated.

ORDER INFORMATION

SERIES	WATTAGE (W)	VOLTAGE UL = 100-277V	COLOR TEMP (CCT)
CPS-EXPR-	40W-	UL-	4000K/5000K
CPS-EXPR-	60W-	UL-	4000K/5000K
CPS-EXPR-	100W-	UL-	4000K/5000K
CPS-EXPR-	150W-	UL-	4000K/5000K
EXAMPLE: CPS-EXPR-60W-UL-50			



Packaging

Part Number	Product Size (in)	Carton Size (in)	Qty/Carton	Net Weight	Gross Weight
CPS-EXPR-40W	7.9 x 6.2 (11.5)	10.7 x 10.7 x 11.1 (17.0)	1	6.7 (8.0) lbs	6.9 (8.6) lbs
CPS-EXPR-60W	11.8 x 8 (13.3)	14.6 x 14.6 x 13.4 (19.3)	1	15.5 (18.1) lbs	17.7 (19.4) lbs
CPS-EXPR-100W	18.1 x 9.6	20.9 x 20.9 x 15.4	1	29.6 lbs	37.9 lbs
CPS-EXPR-150W	18.1 x 9.6	20.9 x 20.9 x 15.4	1	29.6 lbs	37.9 lbs



CPS LED LIGHTING

843-407-6803

SALES@CPSLED.COM


WWW.CPSLED.COM

CPS LED LIGHTING

SPECIFICATIONS

UL 1598 suitable for damp locations, type IC
UL 8750 LED equipment in lighting products
UL 844 Explosion proof certification
IP66 rated
0-10V dimming control wiring included (requires separate 1-10V DC dimming circuit)
Material: Die-cast aluminum housing
Mounting: U-bracket, slipfitter, or wall mount options
Warranty: 5 years
Input voltage: 100V-277V
CRI ≥ 70
Temperature rating: -40°C to $+50^{\circ}\text{C}$ (-40°F to 122°F)
L70 life projected: 100,000 hours
Lens: High transmittance tempered glass
Effective projected area: EPA = 0.61
CCT: 2700K-6500K options
Lumens: 120 lm/W

Photometric Data 120°



CPS LED LIGHTING

843-407-6803

SALES@CPSLED.COM


WWW.CPSLED.COM

CPS LED LIGHTING


Mounting Dimensions:

Wire color







UL:





ATEX:
IECEX:



Ceiling mount/ Drop mount



Wall mount



PA-Stanchion mount



CPS LED LIGHTING
843-407-6803
SALES@CPSLED.COM
WWW.CPSLED.COM