

CPS LED LIGHTING

Applications:

Industrial

Commercial

High bay applications

Warehouses

Retail spaces

Gymnasiums



Slim Linear High Bay

The linear high bay is the lighting solution for a wide variety of applications and mounting heights.

Made with precision designed optics.

UL 1598 damp locations
UL 8750 led equipment in lighting.

ORDER INFORMATION

SERIES	LENGTH (FT)	WATTAGE (W)	VOLTAGE UL = 100-277V	COLOR TEMP (CCT)	
CPS-SLHB-	2-	85W-	UL-	50	
CPS-SLHB-	2-	130W-	UL-	50	
CPS-SLHB-	2-	155W-	UL-	50	
CPS-SLHB-	2-	210W-	UL-	50	As seen on DLC as: CPS-SLHB-4-210W- UL-50
CPS-SLHB-	4-	300W-	UL-	50	
CPS-SLHB-	4-	400W-	UL-	50	
CPS-SLHB-	4-	540W-	UL-	50	
Example: CPS-SLHB-2-155W-UL-50					

DIMENSIONS (IN)

PART NO.	LENGTH	WIDTH	DEPTH	WEIGHT
CPS-SLHB-2-85W	24.8	15	2.2	10 LBS
CPS-SLHB-2-130W	24.8	15	2.2	10 LBS
CPS-SLHB-2-155W	24.8	15	2.2	10 LBS
CPS-SLHB-2-210W	24.8	18.9	2.2	11.3 LBS
CPS-SLHB-4-300W	46.5	18.9	2.2	20 LBS
CPS-SLHB-4-400W	46.5	18.9	2.2	20 LBS
CPS-SLHB-4-540W	46.5	22.9	2.2	22 LBS



CPS LED LIGHTING

843-407-6803

SALES@CPSLED.COM

WWW.CPSLED.COM

CPS LED LIGHTING

Optional Accessories:

V Hook

V Hook + Chain

Cable

Wire guard

Surface

Pendant

Suspending

Emergency

SPECIFICATIONS

UL 1598 suitable for damp locations, type IC

UL 8750 LED equipment in lighting products

Warranty: 7 years

Dimming: 0-10V

Material: Steel plate

Input Voltage: 120-277V

CRI ≥ 80

L70 Life Projected: 50,000 hours

Lens: Frosted

CCT: 3500/4000/5000 K

Lumens: Wattage x 130lm/W

Mounting: suspended

Temperature rating: Ambient temperatures rated for -20°C to 50°C when fixture is suspended at least 18" from ceiling

PHOTOMETRIC TEST LIST

<u>Part No.</u>	<u>Lumens</u>	<u>Watts</u>	<u>Rated</u>
CPS-SLHB-2-85W-UL-40	11475	85	135
CPS-SLHB-2-85W-UL-50	11560	85	136
CPS-SLHB-2-130W-UL-40	17550	130	135
CPS-SLHB-2-130W-UL-50	17680	130	136
CPS-SLHB-2-155W-UL-40	20925	155	135
CPS-SLHB-2-155W-UL-50	21080	155	136
CPS-SLHB-2-210W-UL-40	28350	210	135
CPS-SLHB-2-210W-UL-50	28560	210	136
CPS-SLHB-4-300W-UL-40	40500	300	135
CPS-SLHB-4-300W-UL-50	40800	300	136
CPS-SLHB-4-400W-UL-40	54000	400	135
CPS-SLHB-4-400W-UL-50	54400	400	136
CPS-SLHB-4-540W-UL-40	81000	540	150
CPS-SLHB-4-540W-UL-50	81540	540	151



CPS LED LIGHTING

843-407-6803

SALES@CPSLED.COM

WWW.CPSLED.COM