

# CPS LED LIGHTING

Applications:

Offices

Hallways

Multipurpose Rooms

Conference Rooms



## Tunable Vapor Tight

The tunable vapor tight fixture is built to withstand higher humidities, with a rating of UL 1598, and an impact resistant polycarbonate lens.

With consistent, bright lighting and a easy installation, it makes a great cost effective means of illumination.

## ORDER INFORMATION

SERIES	LENGTH (FT)	WATTAGE (W)	VOLTAGE UL = 100-277V	COLOR TEMP (CCT)
CPS-TVT-	4-	34W/38W/45W-	UL-	3550
	8-	38W/46W/54W-	UL-	3550
<b>EXAMPLE: CPS-TVT-4-34W-UL-3550</b>				
DLC Model# CPS-TVT-4-34W-UL-3550				

## SPECIFICATIONS

UL 1598 suitable for damp locations, type IC

0-10V dimming is continuous

Lumens: 125-127 LM/W

Material: plastic + PC

Mounting: surface, V hook ready

Warranty: 7 years

Input voltage: 100V-277V, 50/60 Hz

Color temperature: 3500K-5000K

Temperature rating: -40°F~+122°F

L70 life projected: 100,000 hours

Lens: frosted



CPS LED LIGHTING

843-407-6803



SALES@CPSLED.COM

WWW.CPSLED.COM

# CPS LED LIGHTING

## PHOTOMETRIC TEST LIST

PART NUMBER	LUMENS-RATED	WATTS-RATED	EFFICACY-RATED	CCT RANGE
CPS-TVT-4-34W/38W/45W-UL-3550	5850	45	130	35-50
	5895	45	131	35-50
	5940	45	132	35-50
	4940	38	130	35-50
	4978	38	131	35-50
	5016	38	132	35-50
	4420	34	130	35-50
	4454	34	131	35-50
	4488	34	132	35-50
CPS-TVT-8-38W/46W/54W-UL-3550	7020	54	130	35-50
	7074	54	131	35-50
	7128	54	132	35-50
	5980	46	130	35-50
	6026	46	131	35-50
	6072	46	132	35-50
	4940	38	130	35-50
	4978	38	131	35-50
	5016	38	132	35-50



## DIMENSIONS

	LENGTH (Inches)	WIDTH (Inches)	DEPTH (Inches)	WEIGHT (lbs)
CPS-TVT-4-34W/38W/45W-UL-3550	47.2	3.54	3.14	4.4
CPS-TVT-8-38W/46W/54W-UL-3550	94.4	3.54	3.14	7.7



CPS LED LIGHTING

843-407-6803

SALES@CPSLED.COM

WWW.CPSLED.COM